CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

WESLEY WESLEY
TRADEWELL 35
ANTIGO, WIS.

Description of corner evidence found:

FOUND BENT R.R. SPIKE AT ROAD INTERSECTION, 4" BELOW SURFACE OF PAVEMENT.
FOUND NO OTHER EVIDENCE. (ROAD HAD BEEN MOVED IN 1957). REPLACED R.R. SPIKE
WITH 3/4" x 24" IRON FORM STAKE DRIVEN FLUSH WITH PAVEMENT.

(CORNER WAS FOUND 5-10-78 AND WITNESSED 9-21-78)

Description of monument and accessories I established to perpetuate the original location of this corner.

		-			x 24 IRON PORM STAKE	
	1 30/4	To I	×	0 - 2"	x 42" BLACK IRON PIPE W/ 8	BRASS
	RIOE RIIE 00	Wine I		A - NA	ALL PLUGON TELEPHONE PO	OLE
	13 18 18 17 18 18 18 18 18 18 18 18 18 18 18 18 18	- b-1 50,	62		ILE PLUG ON POWER POI	
	wc wc	1 1 No.			2	4
	COP SE 59.00	 :	TOWN ROAD	T30 N	1	A
		2 15		RIOZ RIE D	(2)6	Z N
NOTE	BRASS CAPS SET ACROSS	15 10 FOX	50	13 18 12/b	(RL5)	ORT
	FROM EACH OTHER WITH TRANSIT.	0		24 19 or	1342	Z
	RECON COMPASS	6	0	Cop 1111 19 20		7
			200	NW AS		
	Dated at ANTIGO	, Wis., this	3 rd day	of OCTOBER	, 19.78	-•
	Signature Misking J. (County Surveyor,		EGISTERED LAND	Surveyor Regis	tration No. 13A2	
	Office of Register of Deeds, Coun	tv of		I hereby o	certify that the withi	n.
instrument was filed in this office for record on the day of						
	ato'clock M.					
	(Register	of Deeds)				
	P		D			

State of Wisconsin County of LANGLADE I. WESLEY J. TRADEWELL , do hereby certify that on the 10 TH day of 19.78, I found evidence of the NORTH WEST corner of SECTION 19. Township 30 , North, Range 11 EAST , Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner. Resident witnesses:

= Corner monument restored.