			CERTIFIED	LAND	CORNER	RESTORATION
State of Wisconsin	1	***			1.17.1	

SS.

		$\circ$	
Indov	No	1<-1	
IIIUEX	110	1	

History of original corner establishment:



Description of corner evidence found:

FOUND 6" SPIKE IN 2 ND. LAYER OF ASPHALT, COULD FIND NO OTHER EVIDENCE. REPLACED SPIKE WITH A 3/4" x 24" IRON ROD SET FLUSH WITH PAVEMENT. (CORNER FOUND 5/10/78 AND WITNESSED 9/21/78)

Description of monument and	l accessories I	established	to perpetuate	the original	location of	this corner.
-----------------------------	-----------------	-------------	---------------	--------------	-------------	--------------

RIOE RIIE	五	& - NAIL SET IN POWER POLE
/ 100	± 1	O - 2" x 42" BLACK IRON PIPE
V 24 19 17 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	5	WITH BRASS CAP SET
- Ne	< 3/4 × 24" IEON ROD	
COR SE 4485	BEAR LAKE RD. T30N	NOTE: BRASS CAPS SET ACROSS FROM
	RIOE RIIE	EACH OTHER WITH TRANSIT.
= 1	8 (S 24 19 N) 34 25 30 0	BEARINGS TAKEN ON POWER POLES
292, 24	No we do	WITH RECON COMPASS
- 8	O ROP NW 58.	
Dated at ANTIGO	, Wis., this 27th day of	DEPTEMBER, 1978.
Signature AN and Jacobs Granty Surveyor, Registere	Title REGISTERED LAND SURVEYO	ce Registration No. 1342
Office of Register of Deeds, County of	ord on theday of	I hereby certify that the within
at	of the the transfer of the tra	
(Register of Deeds)	)	

..Deputy

I WESLE	1 N. TRA	DE WELL	, do hereby
of	1AY	, 19	78 , I found
evidence of	the5	OUTH WES	<u>T</u>
Township	30 T E	th Duinci	North, Range pal Meridian,
as described	hereon: and	that from	this evidence
			nd accessories
as described	d hereon to		e the original
location of	this corner.		
Resident wi	itnesses:		
	T30N	RIIE	
			1
	1	I	i
	1	1	1
			+
	1	1	ì
		I	!
	1	-9	<u> </u>
		1	1
	1	I	i l
	+		<u> </u>
	Ī		i i
	1	1	1
		I	
0		1	
$\bigcirc$ = Corne	r monument	restored.	

County of LANGLADE