

4 30 11 32 00 10

U. S. PUBLIC LAND SURVEY MONUMENT RECORD

I N S T R U C T I O N S :

This record shall show the location of the corner and shall include all of the following nine elements (a through i).

- (a) Identify the corner by reference to the U.S. public land survey system.  
O = Corner monument restored.

SEC 32  
T 30 N  
R 11 E



- (b) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

E 1/6 COR S. LINE SEC 32 IS SHOWN AS 1" IRON PIPE SET ON SHAWANO CO ASM # 966\* BY R.W. NORON IN 1991, SO I WOULD ASSUME THAT THE S 1/4 COR OF SEC 32 IS ALSO IN PLACE (8/2020 IT IS)

- (c) In the plan view drawing below, provide reference ties to at least 4 witness monuments, or, if the location is within a municipality, to at least 2 witness monuments. (Witness monuments shall be made of concrete, natural stone, iron or other equally durable material.) Describe witness monuments.

\* COPY IN "30-11" FILE

- (d) Show a plan view drawing depicting the relevant monuments and reference ties which is sufficient in detail to enable accurate relocation of the corner monument if the corner monument is disturbed. Indicate north.

D. Tenney  
9/12/94



828