CERTIFIED	LAND	CORNER	RESTORATION	V

Index No. R-9


State of Wisconsin ss. History of original corner establishment:

DRIGINAL CORNER ESTABLISHED BY HIRAM C. FELLOWS IN SEPT., 1860.

Description of corner evidence found:

EST. BY OCCUPATION OF EXISTING

(Register of Deeds)



Milliam S. Pelly

Description of monument and accessories I established to perpetuate the original location of this corner.

1		WIT COR	11/2" BRASS CAP		
4	SET 2-11/2" x 42"	(OR 33' S.	WITNESS MONO		
	BLACK IRON PIPES	SECT COR	, o	SET 1" x 14" IP	
	WITH BRASS CAP	30 1 21	>10	WIR.R. SPIKE IN C	WIT COR
	WITNESS MONUMENTS	29 28	HWY. "C"		COR 50' NW
	,	T32N, R9E /	in	138	SECT COR
HLXO		WFK	201	8 11/2" BRASS	20 + 21 29 28 T32N, R9E
>	PKNAIL & BT		(3)	CAP WITNESS	5-26-81
	& RIBBON -		29" HEMLOCK M	MONUMENT	WFK
Dated at	Ессно	, Wis., this	26世 day of	MAY	, 19. 81
Signature.	Villama Kelly (County Surveyor, Registe		OUNTY SURVEYO other duly authorized officia		n No. <i>10</i> 98
Office of Reg	gister of Deeds, County of			, I hereby certify	that the within
instrument v	vas filed in this office for re-	cord on the	day of		, 19
	'clock M.				

	~		1
\bigcirc =	(orner	monument	restored.

County of LANGLADE

location of this corner.

Resident witnesses:

I WILLIAM F. KELLY, do hereby certify that on the 26th day of MAY, 19.81., I found evidence of the 5ω corner of 5.εςτιοΝ 21.

Township 32, North, Range 9.ΕΑΣΤ, Fourth Principal Meridian, as described hereon; and that from this evidence

I established a new monument and accessories as described hereon to perpetuate the original