

LANGLADE COUNTY U.S. PUBLIC LAND CORNER RESTORATION

The East Quarter corner of Section 31, T. 32 N., R. 11 E., Langlade County, WI.

Corner was: (check all that apply)

43211312000

- Restored through acceptance of an obliterated evidence location.
- Restored through acceptance of a found perpetuated location.
- Determined to be lost and re-established through proportionate methods.
- Show bearings and distances to PLSS corners used for proportioning, and show original distances).
- Restored/recovered/re-established in a location that differs from a previously established position.
- (Show difference in plan view below).
- Check here if additional information is shown on the reverse side of this form.

Describe record evidence, recovered physical evidence, occupational evidence, testimonial evidence and all other evidence considered in the recovery/restoration of the corner.

The original corner was established in 1860 by Hiram Fellows. Original bearing trees: birch, 8", S75°E, 6 links and an elm, 10", N 46° W, 21 links. In 1883, B.F. Dorr found both original bearing trees and set a pine post for the corner. Dorr surveyed and subdivided Section 31, and also did work in adjoining Section 30 as part of the survey of the village of Reeve in 1886. I re-established this corner on a straight line between the adjoining section corners and in line with an old fence just east of the old railroad grade. The corner falls approximately 4 feet west of the center of Railroad Drive. Measurements to occupation lines in Section 31 appear to support this position in regards to Dorr's measurements, with the exception of Dorr's distance to the center of Section 31. I believe his distance to the center of Section 31 is wrong because extrapolation of his east-west distances in the NE 1/4 of Section 31 do not support his distance to the center of Section 31. See my map of Section 31 which I prepared showing Dorr's distances compared to measured distances.

Physical description of the monument set:

I set a Berntsen SN-1 survey marker nail for the corner.

Describe the accessories used to perpetuate the corner. Include a plan view drawing and accessories found/set. Describe measuring point on bearing trees. Show any topographic features that would aid in future recovery of the corner.

