_DTICIED			RESTORATIO	A I
FRICE	1 4 1 1 1 1	LIBINER	REVIORATI	иv

Index	No	F -	- 4
muex	INU.	_	

State of Wisconsin

County of Langlade

State of Wisconsin History of original corner establishment:

PLEOGER

No evidence of any previous corner.

Description of corner evidence found:

Ran traverse from section corner 5, 6, 7, 8 to 1/4 corner between sections 6 and 7 for a distance of 2648.702 feet at bearing S88-32-18W. Set E 1/16 corner 1324.351 feet.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1-1/2" I.D. iron pipe with screw-on brass cap - stamped: Projecting 12" above ground.
Marked NBT's:

Black Ash				
Black Ash	7"	N88°E	13.85	feet
Black Ash	7''	S54°E	15.25	feet
all scribed		1/16 B.T.		

Dated at Rhinelander , Wis., this 23rd day of	March 1081
·	
Signature Oance K. Pleage Title Registered Land Surveyor (County Surveyor, Registered Land Surveyor, or other duly authorized official)	Registration No. 1537
Office of Register of Deeds, County of	
instrument was filed in this office for record on the	, 19
(Register of Deeds)	
D	

O = Corner monument restored.

E 1/16

Daniel K. Pleoger

corner of Sections 6 and 7

location of this corner.

Resident witnesses:

certify that on the 15th day of December , 19 80, I ASSAMS established E 1/16

Township 33, North, Range 9 East, Fourth Principal Meridian, as described hereon; and that from this evidence

I established a new monument and accessories as described hereon to perpetuate the original

T33N R9E