State of Wisconsin	ss.
County of Langlade	
I Daniel K. Plecger certify that on the 26th of March , 10 evidence of the Section corner of 25-36 - 3Q-31 Township 33 9 & 10 East , Fourth Prin	do hereby day 9 82, I found
evidence of the	North Range
9 & 10 East , Fourth Prin as described hereon; and that from	cipal Meridian m this evidence
I established a new monument as described hereon to perpetua	and accessories
location of this corner.	SCONE
Resident witnesses:	DANIEL K. PLEOGER
	S-1537 WINTER, WIS.
~ 10 sec.	SURVERSE

T33N		R9E	
	 	I	s.c.
	 -	I	1
		! !	<u> </u>
	I	' I	
	l S	1 1 36	
	!	-	<u> </u>
	 	i 1	t I
	-	' ·	
	' 	• [
		 	l

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. V-25

History of original corner establishment:

Original corner established by H.C. Fellows, Gov. deputy surveyor in 1860 from which fir 10" bears S40W 44 links, white pine 10" N47W 36 links - spruce 8" N58E 6 links and elm 12" bears S10E 33 links.

Description of corner evidence found:

Recovered a 4" iron pipe filled with concrete and brass cap. Iron pipe is in good condition and securely set. Brass cap is not stamped.

ORT

Spruce stump 11" N48W 23.30 ft. Scribed R9E \$25

Description of monument and accessories I established to perpetuate the original location of this corner.

Stamped brass cap Monument projects 6"	above g	round.			T33N	
Marked NBTs:	, 0			Ξ(25 30	R1
Black ash 7"	S83W	24.09	ft.	R9E	25 30 36 31	Œ
Black ash 6"	N9°W.	17.95	ft.		30 31	
Black ash 7"	N68E	19.18	ft.	S	1537 - 19	982
Scribed	S.C B	.T.				

Dated at	Rhinelander	., Wis., this	22nd	day of	April	, 1982
	Daniel County Surveyor Registere					
nstrument	egister of Deeds, County of was filed in this office for reco o'clock					
	(Register of Deeds)				
			_			