	ERTIFIED	LAND	CORNER	RESTORATION
--	----------	------	--------	-------------

Index No. W-18

State of Wisconsin SS. County of Langlade

Daniel K. Pleoger certify that on the 1st day of March 19 82, I spootk est.

corner of Section 35 Township .........., North, Range 9 East Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the location of this corner.

Resident witnesses:

DANIEL PLEOGER ··S-1537 WINTER, WIS

T33N R9E NW 1/16

O = Corner monument restored.

History of original corner establishment:

No evidence of any previous corner.

Description of corner evidence found:

Corner established by subdivision of NW 1/4. Location of NW 1/16 corner is N86-40-57W 1317.42 ft. of NC 1/16 and NO1-44-09E 1343.21 ft. of WC 1/16.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 2" iron pipe with brass cap stamped:

T36N R14E

Monument projects 18" above ground. Marked NBTs Maple 7" N7°E 6.48 ft.

NW  $1/16^{\frac{S|35}{1}}$ S1537 - 1982

White ash 6" \$81E 2.58 ft. Scribed 1/16 - BT.

Dated at Rhinelander	, Wis., this 23rd	day of	April	, 1982
signature Daniel K. Pleager	Registered	Land Surveyor	Registration	No
(County Surveyor, Registe	red Land Surveyor, or other d	luly authorized official)		
Office of Register of Deeds, County of an astrument was filed in this office for reduct				
(Register of Deec	is)	·····		
g.,	Denu	itv		