
## U. S. PUBLIC LAND SURVEY MONUMENT RECORD

INSTRUCTIONS:

This record shall show the location of the corner and shall include all of the following nine elements (a through i).  $T33N \quad R9E$ 

- (a) Identify the corner by reference to the U.S. public land survey system.
  - O = Corner monument restored.



(b) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

From record search and field evidence determined by old occupational fence line running east and centerline of old section line road, placed quarter section corner at this point.

- (c) In the plan view drawing below, provide reference ties to at least 4 witness monuments, or, if the location is within a municipality, to at least 2 witness monuments. (Witness monuments shall be made of concrete, natural stone, iron or other equally durable material.) Describe witness monuments.
- (d) Show a plan view drawing depicting the relevant monuments and reference ties which is sufficient in detail to enable accurate relocation of the corner monument if the corner monument is disturbed. Indicate north.

T33N R9E R10E

1/4 36 31 W.C.

S45E 46.15 FT. 2 1/2" Iron W.C. S1682-1983 N45W 46.15' pipe w/brass cap Maple 7" 🏠 **3**B-Ash 10" N76E 467 scribed: 1/4-BT scribed: 1/4-BT N54W 33.94 X — Fence Line -X-X-- x — x վ" Iron pipe S44W 43.30' Tyes to #16 Nail in center Y-Birch 8" of trees scribed: 1/4-BT Old Road Centerline

ストレス

(e)	Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished
	by distance and direction. Show the discrepancy on the plan view drawing under (d), above. Show the distances between the corner as previously restored or reestablished
	and (1) the corner as restored or reestablished, and (2) to at least 2 of the witness monuments shown on the drawing in (d), above.

Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location?

Obliterated evidence location

(g&h) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning in determining the corner location?

GLEN
BARKER
S-1682 AND SURVE

Glen Barker

(type or print name) certify that the corner location shown on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

5/18/83

Signature

Date