State of Wisconsin County of Langlade

certify that on the day of August 19.76, I found evidence of the

Township. 33, North, Range 11E Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses:

		^	
		P	1
	1	I	I
1	1	1	1
	l	I	L
l_	1	'	
	ī — — —		I
1 <i>T</i>	133 N 1	RILE	I
l	1		i
C		22	1
7 - 36	Petio w	' <u>X</u>	<u> </u>
	1	ı	1
	l	I	1
ļ	1	1	I
	I	I	I
<u> _ </u>	<u> </u>	'	
	ι —	i	1
	ţ	i	l j
[I	1	1
I	I	I	1
	i	I	1

O = Corner monument restored.

History of original corner establishment:

CERTIFIED LAND CORNER RESTORATION

August 14, 1936

Description of corner evidence found:

4" I RON pipe with DRASS CAP WITNESS CORNER

Description of monument and accessories I established to perpetuate the original location of this corner.

New Bt's to witness Corner

6" Hard Maple NG4W 47.6 FT

4" white Birch Syof 77.1 Ft

22 RSH

22 RSH

22 RSH

22 RSH

22 RSH

4. ()		Pare Aug 14, 1936	
Dated at ANT 190	Wis., this 28 th	o day of	Jugust , 1976
Signature Laument Shall	HTitle Co. St.	and Survey	Registration No. 5685
Dated at	Land Surveyo, or other	duly authorized official	ely certify that the within
instrument was filed in this office for reco	on the	day of	

(Register of Deeds)