## U.S. PUBLIC LAND SURVEY MONUMENT RECORD (Prepared and as required by S. A-E 7.08 W Administrative Code)

The corr	ner of Section $-\frac{1}{2}$	<u>3 , t. 34 n., r. 10 e.</u>	, Langlade County, W
Corner was: (check all that apply)  Restored through acceptance of a  Restored through acceptance of a  Determined to be lost and re—este (Show bearings and distances to Restored/recovered/reestablished is established position. (Show diffe	i found perpetuate ablished through p o PLSS corners us in a location that	d location. proportionate methods. sed for proportioning.) differs from a previously	34/0/32020
☐ Check here if additional information  Describe record evidence, recovered phe  considered in the recovery/restoration	ysical evidence, oc		al evidence and all other evidence
MEAS. W'4 TO E'4 70 MEAS. W'4 TO E'4 70 MEAS. W'4 TO C'43 MEAS. C'4 TO E'43 PROBABLE DORR SET S ALSO STONE; END OF	8.08 CH. (515: 9.31 CH. (259 8.77 CH. (256 STONE 6"×6	3.28') 94.46') 8.28') "SQUARE TOP W/CHI	
Physical description of the monument FOUND STONE W/CHISLE( 2000 DEAN WILLIAMS	_	,	
MORE WOODED LEGEND	MAN-MADE CHANNEL 18'± WIDE 8'-10' DEEP  NARROW WOOD BRIDGE WOOD BRIDGE C''4 SEC. 13-6"*6" STONE W/ X ON TOP (FL O W)	n of the corner. Include a plan aring trees. Show any topogra SET  1"×30"I.P.  N4°05'55'E RED PINE  29.40' PLANTATION  CHUCK HANDEYSIDE HUNTING SHACK  APROX.2  1"I.P. FOUND  S83°55'03"E 20.72'  1"I.P. FOUND S7°56'25"V  18.90'	2568.28'  E 1/4 COR. SEC. 13  1"I. PIN 1.5' BELOW
• I" I. ROD, S, & TOUCHING }	OF DRAINAGE	WOOD	95
STONE W/X ON TOP			The CENTER 1/4
⊙ I"I PIN		SURVEYORS SEAL	corner of Section 13  T. 34 N., R. 10 E.  Langlade County, W
I, DEAN WILLIAMS RLS-2468, corner location shown on this record by me or under my direction and con U.S. Public Land Survey Monument Reand complete to the best of my know Dean Williams  Signature	was determined itrol and that this cord is correct	22468 SUBJECT 1975	Langlade County, W

## WISCONSIN ADMINISTRATIVE CODE

A-E 7.07 Monuments. The type and position of monuments to be set on any survey shall be determined by the nature of the survey, the permanency required, the nature of the terrain, the cadastral features involved, and the availability of material. History: Cr. Register, February, 1987. No. 374, eff. 3-1-87.

## A-E 7.08 U.S. public land survey monument record.

- (1) WHEN MONUMENT RECORD REQUIRED. A U.S. public land survey monument shall be prepared and filed with the county surveyor's office as part of any land survey which includes or requires the perpetuation, restoration, reestablishment or use of a U.S. public land survey corner, and,
- (a) There is no U.S. public land survey monument record for the corner on file in the office of the county surveyor or the register of deeds for the county in which the corner is located; or,
- (b) The land surveyor who performs the survey accepts a location for the U.S. public land survey corner which differs from that shown on a U.S. public land survey monument record filed in the office of the county surveyor or register of deeds for the county in which the corner is located, or,
- (c) The witness ties or U.S. public land survey monument referenced in an existing U.S. public land survey monument record have been destroyed or disturbed.
- (2) FORM REQUIRED. A U.S. public land survey monument record shall be prepared on the board-approved form or on a form substantially the same as the board-approved form which includes all the elements required by this section. A form used for this purpose shall be entitled, "U.S. Public Land Survey Monument Record".

Note: A copy of the board-approved form is available from the Department of Regulation and Licensing, Bureau of Business and Design Professions, 1400 East Washington Avenue, PO. Box 8935, Madison, Wisconsin 53708.

- (3) MONUMENT RECORD REQUIREMENTS. A U.S. public land survey monument record shall show the location of the corner and shall include all of the following elements:
- (a) The identity of the corner, as referenced to the U.S. public land survey system;
- (b) A description of any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence considered by the surveyor, and whether the monument was found or placed;
- (c) Reference ties to at least 4 witness monuments. Witness monuments shall be concrete, natural stone, iron, bearing trees or other equally durable material, except wood other than bearing trees;
- (d) A plan view drawing depicting the relevant monuments and reference ties which is sufficient in detail to enable accurate relocation of the corner monument if the corner monument is disturbed;
- (e) A description of any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished;
- (f) Whether the corner was restored through acceptance of an obliterated evidence location or a found perpetuated location;
- (g) Whether the corner was reestablished through lost-cornerproportionate methods;
- (h) The directions and distances to other public land survey corners which were used as evidence or used for proportioning in determining the corner location; and,
- (i) The stamp and signature or seal and signature of the land surveyor under whose direction and control the corner location was determined and a statement certifying that the U.S. public land survey monument record is correct and complete to the best of his or her knowledge and belief.

History: Cr. Register, February, 1987. No. 374, eff. 3-1-87; am. (1) and (3) (c), Register, May, 1989. No. 401, eff. 6-1-89.