•••••	
•••••	
	_

PRTIFIFD	CORNER	RESTORATION
JEIN I II I I I I I I I I I I I I I I I I	COMMEN	NESIGNATION

34-10		
Index No	Q	-5


 $\left. \begin{array}{c} \text{State of Wisconsin} \\ \text{County of} \quad \textbf{Langlade} \end{array} \right\} \text{ss.}$

Raymond J. Hallisy, do hereby certify that on the 8th day of June, 19 68, I found evidence of the S 1/16

corner of Section 19
Township 34 , North, Range
10 , Fourth, Principal Meridian,
as described hereon; and that from this evidence
I established a new monument and accessories
as described hereon to perpetuate the original

location of this corner.

Resident witnesses:



O = Corner monument restored.

History of original corner establishment:

Corner set in the 1930's by: C. W. Borth

E. F. Kowalke D. A. Hintz

Description of corner evidence found:

Found squared stake down, point intact. IN FIELD Stake marked S 1/16

Description of monument and accessories I established to perpetuate the original location of this corner.

Set Std. $1\frac{1}{2}$ pips with cap marked S 1/16 19 20

0 \$ 1P

10" cherry S 52°W 136'8"

04 6" cherry 310°W 86'3"

Signature William Title Title That Surveyor, Register Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of The Manager County of The Manage