

CERTIFIED LAND CORNER RESTORATION

Index No. S-17

State of Wisconsin }
County of Langlade } ss.

History of original corner establishment:


Corner established in 1937 by Langlade County surveyors.

I Daniel K. Pleoger, do hereby certify that on the 29th day of October, 1980, I ~~found~~ established evidence of the N 1/16 corner of sections 26 and 27 Township 34, North, Range 10 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Description of corner evidence found:

Recovered old 5" squared cedar post scribed N 1/16 - S26 - N 1/16 S27 which bears north 2.00 feet of new position. Ran traverse from section corner 22, 23, 26, 27 to 1/4 corner between sections 26 and 27 for a distance of 2617.932 feet at bearing N 1-48-02 E. Set N 1/16 corner 1308.966 feet intermediate.

Resident witnesses:



Description of monument and accessories I established to perpetuate the original location of this corner.


Set a 1-1/2" I.D. iron pipe with screw-on brass cap - stamped: Projecting 18" above ground.

Marked NBT's -

Maple 7" N34°W 20.15 feet
Maple 6" N64°E 15.38 feet scribed 1/16 BT
Maple 7" N86°W 40.75 feet

T34N R10E
N 1/16 27+26
S1537-1980

FORM 983 H. C. MILLER CO., MILWAUKEE



○ = Corner monument restored.

Dated at Rhinelander, Wis., this 23rd day of February, 1981

Signature Daniel K. Pleoger Title Registered Land Surveyor Registration No. 1537
(County Surveyor, Registered Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of _____, I hereby certify that the within instrument was filed in this office for record on the _____ day of _____, 19____ at _____ o'clock _____ M.

(Register of Deeds)

By _____ Deputy