CERTIFIED LAND CORNER RESTORATION

Index No. Z-14

History of original corner establishment:

SS.

No evidence of any previous corner.



Description of corner evidence found:

Corner established by traverse and computation. Ran traverse from section corner $\begin{array}{c} 33-34-34-10 \\ 4-3-33-10 \end{array}$ to between sections 34-3 T33 & 34N R10E for a distance of 2692.071 feet at bearing S88-51-44W. Set W 1/16 corner 1346.086 intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1-1/2" I.D. iron pipe with screw-on brass cap, stamped: Monument projecting 18" above ground.

Marked NBT's -

Black Spruce 6" N33W 9.88 feet Black Spruce 5" S47W 5.05 feet Black Spruce 6" S53E 11.37 feet

T34N R10E $\frac{V}{1/16} = \frac{S}{S} + \frac{34}{3}$ T33N R10E S1537-1980

Dated at.	Rhinelander	, Wis., this	4th	day of	December	, 19.80
Signature.	Daruil K. Pleog (County Surveyor, Rep	Title Rogistered Land Surveyo	egistered or, or other du	Land Surve	yor F	Registration No. S-1537
instrumen	Register of Deeds, County at was filed in this office for co'clock					
	(Register of	Dceds)				
_			ъ.			