SS.

Resident witnesses:

DANIEL

K.

PLEOGER

\$-1537

ARTIGO. WIS.

T34N R10E

T34N R10E

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. W-19

History of original corner establishment:

No record of previous survey.

Description of corner evidence found:

Corner established by running traverse from old C 1/4 corner to 1/4 corner between sections 26 and 35 for a distance of 2642.917 feet at bearing N 4-51-41 E. Set NC 1/16 1321.458 feet intermediate.

An old 4" squared cedar post, not scribed, bears ${\rm N48}^{\rm O}{\rm W}$ 4.25 feet from our corner position.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1-1/2" I.D. iron pipe with screw-on brass cap - stamped: Projecting 12" above ground.

Marked NBT's:

Maple 6" N71°E 18.95 feet

Oak 6" S48^OE 19.32 feet scribed 1/16 BT Oak 8" N56^OW 16.82 feet T34N R10E NC 1/16 + 35

S1537-1980

Dated at Rhinelander , Wis., this 25th day of February , 1981

Signature Danie F. Fleogre- Title Registered Land Surveyor Registration No. 1537

(County Surveyor, Registered Land Surveyor, or other duly authorized official)

(Register of Deeds)

By......Deput