## U. S. PUBLIC LAND SURVEY MONUMENT RECORD


INSTRUCTIONS:

This record shall show the location of the corner and shall include all of the following nine elements (a through i).

(a) Identify the corner by reference to the U.S. public land survey system.

O = Corner monument restored.

This corner was originally set by William E. Daugherty and was perpetuated by Robert J. Poss in 1969.




(b) Describe any record evidence, monument evidence, occupational evidence, testimonial evidence or any other material evidence you considered, and whether the monument was found or placed.

We re-tied this corner to perpetuate its location and to make it easier to locate for future users.

(c) In the plan view drawing below, provide reference ties to at least 4 witness monuments, or, if the location is within a municipality, to at least 2 witness monuments. (Witness monuments shall be made of concrete, natural stone, iron or other equally durable material.)

Describe witness monuments.

(d) Show a plan view drawing depicting the relevant monuments and reference ties which is sufficient in detail to enable accurate relocation of the corner monument if the corner monument is disturbed. Indicate north.



A=N14°E -30.49° B=N37°E - 9.52° C=N75°W-5.02° D=N73°W-29.68° Describe any material discrepancy between the location of the corner as restored or reestablished and the location of that corner as previously restored or reestablished by distance and direction. Show the discrepancy on the plan view drawing under (d), above. Show the distances between the corner as previously restored or reestablished and (1) the corner as restored or reestablished, and (2) to at least 2 of the witness monuments shown on the drawing in (d), above.

NA

(f) Was the corner restored through acceptance of (1) an obliterated evidence location, or, (2) a found perpetuated location.?

2/

(g & h) Was the corner reestablished through lost corner proportionate methods? If so, show the method, including the directions and distances to other public land survey corners used as evidence or used for proportioning in determining the corner location.

|  | (i) | 1 | DAN | HIGGINBOTHI | 9 M |
|--|-----|---|-----|-------------|-----|
|--|-----|---|-----|-------------|-----|

(type or print name)

certify that the corner location shown on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Men Hyginbolis.

1-10-95

Date



| State of Wisconsin  County of ANGLADE  I. LOBERT JOSS, do hereby certify that on the 1474 day of 1969, I found evidence of the 5ECTION corner of SECS. 15, 16, 21-22  Township 34 North, Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.  Resident witnesses: |         |  |  |  |  |  |  |  |  |
|---|---------|--|--|--|--|--|--|--|--|
| SEG.21  | 3EC.122 |  |  |  |  |  |  |  |  |

O = Corner monument restored.

## CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

ROBERT
POSS
S-0001
ELCHO, WISCOMSN

94-11

Description of corner evidence found:

FOUND IRON PIPE AT FENCE COR, I W. BIRCH WITH OLD SCARS-BUT FACE ROTTED AWAY. A SECOND BIRCH APPEARS TO BE B.T. BUT TOO BADLY ROTTED

Description of monument and accessories I established to perpetuate the original location of this corner.

| 1: W. BIRCH 28 N30E 14.5 (BADLY SCARRED)  2: BALSAM 6" 9.4  3: W. BIRCH ZO N 68' E 30.0 (SENCES X | CORNER IS<br>I''Z"PIPE PAINTED ORANGE<br>CAP MK: |
|---|--|
| 3: W. BIRCH ZO NGB'E 30.0 FENCES 4. BALSAM 6"N8OW 5.4 OLD FENCES 5. BALSAM 8"574" W 15.0 3        | SEC. COR.  16   15  21   22                      |
| C35  PIPE IS 0.4' So. of FENCE CO   | R.   |

| Dated at ELCHO  | , Wis., this | 14TH                     | dav of                        | JUNE        | 19 69        |
|---|--------------|--------------------------|-------------------------------|-------------|--------------|
| Signature County Surveyor, Regist   | Title RE     | q. Land<br>or other duly | Surveyor authorized official) | Registratio | n No. 5-0001 |
| Office of Register of Decds, County of nstrument was filed in this office for r |              |                          |                               |             |              |
| tM.   |              |                          |                               |             |              |
| (Register of De   | orls)        |                          |                               |             |              |