S-1682

T34N R11E

CPI-1983

History of original corner establishment: SS.

No evidence of any previous corner.

Description of corner evidence found:

Sugar 6" S16W 26.18' scribed 1/16 B.T.

Total distance from C 1/4 section 17 to re-established 1/4 corner between sections 17 and 20 is 3466.32 feet.

Set SC 1/16 1733.16 feet intermediate.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 1" iron pipe with 2" diameter alloy cap - stamped: Set monument flush with the ground as position falls in centerline of logging road. Marked NBTs: Sugar 7" N67E 32.45' sc $1/16 \, {}^{S} + {}^{17}$

Dated at Rhinelander	, Wis., this	19th	day of	Decemb	er , 19 83
Signature Signature Surveyor, Registere	TitleR	egistered or, or other dul	Land Surv y authorized off	eyor ficial)	Registration No.S-1682
Office of Register of Deeds, County of				, I he	reby certify that the within
instrument was filed in this office for reco	ord on the		day of	f	, 19
at			·		

(Register of Deeds)

State of Wisconsin County of Langlade

I Glen Barker , do hereby certify that on the 25th day of October , 19.83 , Infanted established SC 1/16 corner of Section 17 Township.........., North, Range11 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original location of this corner.

Resident witnesses: J. Claflin, Reg. Kand Suckeybr BARKER S-1682 H. Wagoner CRANDON

	T34N	R11E	
'		I	1
1		l	
1		l	l
		!	<u> </u>
!		l	
!		l	
'		ŀ	
'	S	17	
 		¦=	¦
1		I	
i i		I	
1		1/16	
		SC 1/16	
<u> </u>		p	
į .		I	
1		i	
1	·	I	ı İ
		1 .	1

O = Corner monument restored.