rected line, S0°24'E, 19.90 chains from N-1/4 corner.

History of original corner establishment:

State of Wisconsin SS.

I Philip T. Hansen do hereby 18th certify that on the nc-1/16 19 76 , I formed February Section 30 corner of... 34 , North, Range 11 East, Fourth Principal Meridian, as described hereon; and that from this evidence I established a new monument and accessories as described hereon to perpetuate the original

location of this corner.

Resident witnesses: PHILIP T. Glen Barker ARGONNE, Jim Claflin Herb Wagoner ∜

	T34N	R11E	
 	19.90	1	
 	1	NC-1/16 	-
!	19901	! !	
	S	_30 ;	-
! !		 	
 -	¦	 	-
1	 	1 1 1	

O = Corner monument restored.

Description of monument and accessories I established to perpetuate the original location of this corner. Set a 2" iron pipe with brass cap stamped -

Description of corner evidence found: Established the NC-1/16 corner from previously established

C-1/4 and N-1/4 corner. Set corner equidistant between C-1/4 corner and N-1/4 on cor-

Pipe projects 1" above ground level.

scribed 1/16 BT NBT's - Cedar 7" 86.2 links N79°W Cedar 10" 59.4 links scribed 1/16 BT

s 30 NC-1/16 1976

S498 T34N, R11E

Pipe and BT's painted blue.

, Wis., this 4th day of March , 19.76 Rhinelander

ulio Hancen Title Registered Land Surveyor Registration No. S-498 (County Surveyor, Registered Land Surveyor, or other duly authorized official)

Office of Register of Deeds, County of Langlade , I hereby certify that the within at o'clock M.

(Register of Deeds)