U.S.	PUBLIC LAND S	URVEY MONUMEN	T RECORD
Public Land S	urvey Monument Record (3) (a) (b	equirements of Wisconsin Administra ) (c) (d) (e) (f) (g) (h) (i). An additional	ative Code, Chapter A-E 7.08 U.S sheet may be added if necessary to
	sald requirements. n: Township <u>35</u> North	1	
	Range 9 East/We	est	
Town/City/Village			
County	Oneida		Section_34
(material, testi not accepted reestablished	monial, occupational, plats, or if nothing was found, s through lost corner propor	d at this corner and if it was a records, other monuments) use tate evidence used as basis tionate methods, indicate all type of monument found of	ed as a basis for accepting. I for establishing location. I monuments, distances and
2	4" Lynn, N30°E, 9 Links (5	for Section Corner and made in 5.94') 9" Sugar, S45°W, 12 (10.56') 28" Red Oak, N82°W,	2 Links (7.92')
		BT - a stump S45°W, 12 Link cap and made one new references Links (23.1')	
12/28/1976 -	8" Black Cherry, N11°W, 2	iron pipe/brass cap and made 25.0' 6" White Birch, So 39°W, 35.45' 4' x 2' Grey Bo	63°W, 35.45'
8/25/1994 -	to Maple in error.	ment tipped badly; Birch BT ground, made new references	
established codisputed corner  1) 2" x 60" 2) 4' x 5'	orner, show the distances b	s reference.)	disagreement with previously also indicate the ties to the
W41- F 6		. 🗷	SCUNSIN #

(i) I, Milo E. Steran

(type or print name) certify that the corner location on this record was determined by me or under my direction and control and that this U.S. Public Land Survey Monument Record is correct and complete to the best of my knowledge and belief.

Mile E Stefan
Signature

10/9/94 Date



A 13 - 34-9

Stamp

certify that on the	
I WILLIAM F. KEL	<u>∟</u> У, do
County of LANGLADE	∫ 3.
State of Wisconsin	} .

Resident witnesses:

T. 34 N R. 9 E.					
Ψ			1		
	<b>.</b> I i	<b>'</b>	<u>'</u>		
	I	Ì	ı		
		·	<u> </u>		
l	' 		I ;		
į	I	1	1		
	_		!		
	{	<b>F</b> -	<del> </del>		
	1	ſ	1		
	  -	1	1		
ŀ	! !	l !	\ L		
	ī — — — —		1		
1	i I	[ !	1 1		
	' 	i İ	!		
	1	I	l		

O = Corner monument restored.

## CERTIFIED LAND CORNER RESTORATION

History of original corner establishment:

Description of corner evidence found:

FOUND MONUMENT LYING ON ITS SIDE.

SECT. COR. 7.35 N. ON THE COUNTY LINE.

4 3
T.34N.



