0.0.0	of Wi	scons	sin)				
County of	Lang	lade		} ss.				
ertify that of Oct evidence of corner of S Cownship II East as described establishe as described cocation of t Resident wi Glen Bark Jim Claf	on the tober the 35. hereon; da new l hereon this corne	Sect a 31, - 34 Fourth and tha monur to per r.	23rd, 19.76 ion, 8 226 Principat from to the ment and petuate Competition of the petuat	Morth, Range al Meridian, this evidence d accessories the original NNE,				
Herb Wagoner S.498 6 2-								
		N Y	, QQ	2000 U Z	7			
		South Street	O SU	RVE RVE	9			
	T34N	R11	SU	RVE	9			
sc	T34N	R11	SU	RVE RVE	7			
	T34N	R11	O SU	SEN NNE, ξΣ S. 98 9 Q-	9			
	1	R111	O SU	8.90.9.90.10 S	9			
	1	R11	O SU	8.90.9.90 PVE	7			
	1	R111	O SU	RVE	7			
	1	R111	SU	RVE	7			
	1	R11:	SU	RVE	7			
	1	R11:	SU	RVE	7			
	1	R111	SU	RVE	7			
	1		SU	RVE	7			
	1		SU	RVE	7			
	1		SU	RVE	7			
	1		SU	RVE	9			
	1		SU	RVE	9			
	1		SU	RVE	7			
	1		SU SU	RVE	9			
	1		SU SU	RVE	7			
	1		SU	RVE	<i>4</i>			

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. A-5

History of original corner establishment:

Original corner established by Hiram C. Fellows, Deputy Surveyor, in 1859 from which white birch 8" bears N 23° W 20 links; aspen 8" bears N 43° E 29 links; cedar 12" bears S 81° E 25 links; white birch 8" bears S 69° W, 25 links.

No records of any subsequent survey.

Description of corner evidence found:

Recovered a very old 1-3/4" iron pipe projecting 24" above ground (origin unknown). Wm. Kelley, Langlade County Surveyor, states that this pipe has been recognized and used by local land owners for many years.

Searched for evidence of BT's, but found nothing.

Used this corner for control on traverse and computation of north line of Section 5.

Description of monument and accessories I established to perpetuate the original location of this corner.

Replaced old iron pipe with 2½" iron pipe with screw-in brass cap (Langlade County monument) projecting 18" above ground. Cap stamped:

Corner sets 2.80 chains south of Pedro Creek.

Marked NBT's - Sugar 6" N70°E 30.7 feet

Sugar 5" N52°E 15.62 feet

W. Birch 5" N69°W 24.09 feet

W. Birch 8" S14°W 32.71 feet

all scribed SC BT

T35N R11E

Sec. 31 32

Sec. 46 5

T34N R11E

S498-1978

Dated at Rhinelander	., Wis., this30 th	day of	ober , 19 78
Signature Julio J. Hansen. Jounty Surveyor, Registered	Title Registered	Land Surveyor	Registration No. S-498
County Surveyor, Registere	ed Land Surveyor, or other duly	y authorized omciai)	
Office of Register of Deeds, County of	Langlade	, I h	ereby certify that the within
instrument was filed in this office for reco			
(Register of Deeds)		