			ss.
County ofI	anglade.		. } •••
Philip certify that o	T. Hanse	n 7th	., do hereby day
of Apri	1	, 19.7	6 I found
evidence of th	ne Secti	on.	, 1 104
corner of Se	c. 32-33	-5-4	
l'ownship	34 & 35	, N	orth, Range
11 East		urth Principa	al Meridian,
is described h		l that from t	his evidence
established		onument and	accessories
s described		perpetuate	the original
ocation of th		SSEC CO	al Meridian, his evidence accessories the original T.
Resident witr	100000	PHILIP	S
esident with	nesses:	o PHILIP	T 3 2 1
Hen Barke	r /	HANSE	1. 3
	4 ₹₹	ARGONN	E Σ>
Jim Clafli	n (
T. 7	W ~	WIS. S-498	
Herb Wagon	er 🐧 😽	1	595000
	4.7	1/ A "DANAMED	5° , \(\(\(\(\) \)
	No.	SUR	VE 'S
	No.	WIS. S-498 NO SUR	NE, SE
	Y T341	SUR	15, E
SC .	T341	SUR	NE SEE
SC !	T341	WIS. S-498 VO SUR VRILE	ME, S
SC ,	T341	SUR	VE, SE
SC I	T341	SUR	VE,
SC !	T341	SUR RITE	VE Y
SC	T341	SUR	VE Y
SC		SUR	VE Y
SC :	T341	SUR SUR	VE Y
SC !		SUR RITE	VE Y
SC		SUR RITE	VE YE
SC		SUR	VE YE
SC		SUR	VE Y
SC		SUR	VE \
SC		SUR	VE \
SC		SUR	VE \
SC		SUR R11E 	VE \

State of Wisconsin

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. A-9

History of original corner establishment: Original corner established by Hiram C. Fellows, Deputy Surveyor, in 1859, from which W.Pine 16" bears N32°E, 8 lks, white pine 14" bears 568°E 9 lks, Hemlock 9" bears N50°W 21 lks and Hemlock 8" bears 541°W 24 lks. Corner recovered by Vaughn in 1901, but the original BTs as called for did not correspond to the BTs recovered.

Corner recovered by H.C. Lawrence in 1952. No record of who established the corner, but

may have been Chas. Borth. This corner has been recognized for years.

Set a 5" cedar post, and marked NBTs - Y.Birch 10" N60°E 84 lks and Maple 8" S89°E 30 lks.

Description of corner evidence found: Recovered 5" cedar post, squared and scribed S4, S5, S32 and S33 in fair condition. Found a rock cairn around base.

Recovered OBT, Yellow Birch 10" N60°E 84 lks, now a decayed stump, Maple 8" (10") S89°E 30 lks. scribed S4, bottom scribe grown over.

Description of monument and accessories I established to perpetuate the original location of this corner.

Replaced wood post with 2½" iron pipe with brass cap, stamped.

Post projects 2' above ground.

NBTs - Maple 7" S63°W, 64.9 lks, scribed SC BT.

Maple 6" S47°E, 29 lks scribed SC BT.

No others suitable for BTs.

Replaced rock cairn around base of monument.

Pipe and BTs painted blue.

S498

T35N R11E

S32 S33

S51 S4

T34N R11E

1976

Dated at Rhinelander	, Wis., this 12t	hday of	May	, 19.76
Signature Michigan Johnson (County Surveyor, Registr	Title Regist	tered Land Sur	veyor Reg	gistration No. 5-498
(County Surveyor, Regist	ered Land Surveyor, or o	other duly authorized o	official)	
Office of Register of Deeds, County of	Langlade		I hereby	certify that the within
instrument was filed in this office for real at	ecord on the	day	of	, 19
(Register of Dee	eds)			
By		Deputy		