State of Wisconsin

of November , 19 78 , I found re-established www.w.w.w. W 1/16

Township 34.6.35 North, Range 11.East Fourth Principal Meridian, as described hereon; and that from this evidence

I established a new monument and accessories

as described hereon to perpetuate the original

County of Langlade

Philip T. Hansen certify that on the 1

SS.

... do hereby

ARGONNE,

S-498

0	=	Corner	monument	restored
---	---	--------	----------	----------

CERTIFIED LAND CORNER RESTORATION

Index No. A -6

History of original corner establishment:

No records of any previous surveys.

Description of corner evidence found:

No evidence of any corner recovered.

Corner established by traverse and computation. Ran traverse from section corner 31, 32, 5 and 6, east 5604.256 feet to section corner 4, 5, 32, 33. Computed bearing N 89° 13' 25" E. Set 1/4 corner at 2802.128 feet intermediate. Set W 1/16 corner at 1401.064' intermediate between 1/4 corner and section corner.

Description of monument and accessories I established to perpetuate the original location of this corner. Set a 2" iron pipe with screw-in brass cap (Langlade County) projecting 18" above ground -- stamped:

Marked NBI			_			
W. Ash	5"	s34°	² W 3	3.6	fee	et
Sugar	5"	due	west	16	•43	feet
both	scr	ibed	1/16	BT		

	T35N	RILE
	1/16 S.	32
W	1/16 S+	- 5
	T34N	R11E
	5498 -	1978

	Rhinelander					
Signature.	Keljo G. Hansen. (County Surveyor, Registere	Title d Land Surve	Registered	Land Surve	eyor Registra	tion No. S-498
instrument	gister of Deeds, County of was filed in this office for reco 'clock				, i nereby ceru	ny that the within
·	(Register of Deeds)	······		. .		
_			ъ.			