		} ss.
County of Langlad	e	5 33.
Philip T. Hanse Pertify that on the 20 April Peril Per	n 8th	, do hereby
of April	, 19?	Ω, I found
evidence of theE.1/1	. p.	
Cownship34. & .35	N	orth, Range
11 East For	urth Princip	al Meridian,
is described hereon; and		
established a new mo	nument and	l accessories
s described hereon to ocation of this corner.	perpetuate	the original
ocation of this corner.	252525XX	MARINE
Resident witnesses:	5 0 000	S
Hen Barker	PHILI	the original N S P T. SEN
Jim Claflin 🕺 🖧	ARGOI	NNE.
derb Wagoner	S A	.98
47	`~\\` ``-	
***	WI S. A	CONF.
W	TNO SL	IRVE CO
T34N F	OLIE SU	RV
T34N F	20.29	20.29
T34N F	20.29	RV
T34N F	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29
	20.29	20.29

State of Wisconsin

O = Corner monument restored.

CERTIFIED LAND CORNER RESTORATION

Index No. **A-12**

History of original corner establishment: Corner established by H.C. Lawrence, Registered Land Surveyor, during his retracement survey in 1948. He recovered a 4" hemlock post, witnessed by a hemlock 16" S53°E 14 lks, and a y.birch 18" N64° + 7 lks for 1/4 corner at 40.58 chains west of section corner 33 and 34.

Set a 5" cedar post at 20.29 lks, 32 lks south for E 1/16, marked NBTs, W.Birch 10" N10° H 45 lks, W.Birch 9" S5°E 27½ lks. True bearing of line N88° 24' w.

Description of corner evidence found: Recovered 5" cedar post, squared and scribed E 1/16 S4, E 1/16 S33, corner was not in correct position, as it was believed to have been moved because of logging operations.

Set a temporary point from recovered BTs and established correct position by chaining east from 1/4 corner distance of 20.29 chains.

Recovered OBT W.Birch 10" (12") N 10° W 45 lks, scribed S33 BT.

W.Birch 9" (10") S 3° E 27.5 lks, scribed S4 BT.

Description of monument and accessories I established to perpetuate the original location of this corner.

Set a 2" iron pipe with brass cap stamped.

Pipe projects 18" above ground level.

Placed a rock cairn around base of monument.

NBT Sugar 6" N36°W 30.5 lks scribed 1/16 BT.

Pipe and BTs painted blue.

S498 T35N R11E E 1/16 S 33 S 4 1976

Dated at hinelander,	Wis., this 14th	day ofMay	19.70
Signature Hulep J. Alanson. (County Surveyor, Registered	Title Registered	i Land Surveyor	Registration No. 5-498
Office of Register of Deeds, County of instrument was filed in this office for reco	Langlade	, I	hereby certify that the within
at	id on the		, •/
(Register of Deeds)			
Ву		ity	